

Open Class Rules:



These Rules are in addition to the General Driver, Race & Pit Rules. If you are in violation of any rules you will be subject one or more of the following: Removal from the grounds, suspended from racing in one race and/or up to the whole season, suspended from racing at the track indefinitely

Safety Items

1. Drivers must have a full helmet, full fire suit, and enclosed shoes to enter the racetrack (gloves recommended)
2. 4- or 5-point racing harness required. Racing seat mandatory and must be securely fastened on bottom and back of seat. Seat should not have any movement when mounted.
3. 4-point roll cage required. All bars must be within the front and rear firewall.
4. Drivers compartment can be reinforced. FOUR POINT CAGE WITH DOOR BARS ON BOTH SIDES ARE MANDATORY. ANY DRIVERS DOOR PROTECTION DEEMED SAFE BY OFFICIALS ARE LEGAL.
5. RACEceivers mandatory. Can purchase from track for \$90 or rent at \$25 per race from pit shack. Call in advance to ensure availability.
6. All glass must be removed. No loose objects allowed in the car.
7. Bumpers must be in place. No exceptions. Must have working brakes on driven wheels at a minimum.
8. Must have a protective screen or at least 3 ¼" bars on driver's side of front window.
9. Must have functioning window net on driver's window.
10. Must be able to open hood and trunk for inspection.
11. All cars must have steel firewall and any holes must be covered with steel.
12. All driveshafts must be painted white for visibility in case they come off. Must have drive shaft loop.

Vehicle Set up

1. No 4x4's or Pick-ups No Aluminum Blocks. Headers are allowed. Aluminum heads allowed.
2. All hoods/trunks must be pinned shut (no nut/bolt combinations or chains)
3. GAS TANKS: Fuel cells in the trunk are mandatory. Original gas tank must be removed FUEL CELLS ONLY. If you run alcohol it needs to be brought up at the drivers meeting. You must run additive to see it burn. Must have a rollover valve. fuel line through cockpit needs to be inside a secured steel conduit.
4. Cars may be re-enforced. No bolts or other objects protruding from sides of car will be allowed.
5. Radiators in original position only. No cattle catchers. 1-inch lug nuts are mandatory.
6. BATTERIES: Batteries are recommended to be under the hood and moved from the original position. Battery may be on passenger side floorboard if it is in a steel box with a lid. Must be covered and securely fastened.
7. Tranny coolers are allowed but are not to be in the drivers compartment. Water Coolers are allowed.
8. Ballast and weight jacks legal. Must be painted white with car # on the weight. One shock and spring per wheel. No pan hard bars, traction bars, torque links or other traction devices. Quick-change rear ends allowed. No traction control in MSD. All suspension parts must be in stock except for shocks. After market front A frames allowed.
9. Rear end spider gears may be welded. Air cleaner with element must be in place.
10. No profanity or anything officials determine to be inappropriate allowed on or in the car.

WE ARE NOT RESPONSIBLE FOR ACCIDENTS.